

1       **In the Claims**

2       Claims 1 and 15 are currently amended.

3       Claims 1-30 remain in the application for consideration and are listed as  
4 follows:

5  
6       1.   (Currently Amended) A system comprising:

7       an adapter designed to attach to a mobile device, the adapter having one or  
8 more electrical contacts to interface with one or more electrical contacts of the  
9 mobile device when the adapter is attached to the mobile device to allow  
10 information to be passed between the adapter and the mobile device, the adapter  
11 further having a connector portion that is electrically coupled to the one or more  
12 electrical contacts of the adapter; and

13       a host device having a connector portion that is a mate to the connector  
14 portion of the adapter, wherein the connector portion of the host device has one or  
15 more electrical contacts to interface with one or more electrical contacts of the  
16 connector portion of the adapter when the adapter and host device are connected  
17 using the connector portions of the adapter and host device;

18       wherein the adapter is designed to remain continually attached to the  
19 mobile device, including when the adapter is not attached to the host device.

20  
21       2.   (Original) A system as recited in claim 1, wherein the adapter  
22 comprises a glove.  
23  
24  
25

1           3.   (Original) A system as recited in claim 1, wherein the connector  
2 portions of the adapter and the host device together comprise a jack knife  
3 connector.

4  
5           4.   (Original) A system as recited in claim 1, wherein the connector  
6 portion of the adapter comprises a slot portion of a jack knife connector, and  
7 wherein the connector portion of the host device comprises a blade portion of the  
8 jack knife connector.

9  
10          5.   (Original) A system as recited in claim 1, further comprising a  
11 latching mechanism that locks together the connector portions of the adapter and  
12 the host device.

13  
14          6.   (Original) A system as recited in claim 5, wherein the latching  
15 mechanism comprises a spring-loaded ball and dimple mechanism.

16  
17          7.   (Original) A system as recited in claim 1, wherein the connector  
18 portion of the host device comprises a connector assembly made up of a housing, a  
19 connector sub-assembly that includes the one or more electrical contacts of the  
20 connector portion, and a plate holding the connector sub-assembly in place.

21  
22          8.   (Original) A system as recited in claim 1, wherein the connector  
23 portion of the adapter and the electrical contacts of the adapter are both part of a  
24 flex circuit mounted in the adapter.

1           9.     (Original) A system as recited in claim 1, wherein the host device is  
2 designed to be removably coupled to a vehicle.

3  
4           10.    (Original) A system as recited in claim 9, wherein the host device is  
5 designed to be removably coupled to a cigarette lighter jack of the vehicle.

6  
7           11.    (Original) A system as recited in claim 1, further comprising a  
8 plurality of additional adapters each designed to attach to a different one of a  
9 plurality of different mobile devices, wherein each of the plurality of different  
10 mobile device designs has one or more electrical contacts in different  
11 configurations.

12  
13           12.    (Original) A system as recited in claim 1, wherein the mobile device  
14 comprises a cellular phone.

15  
16           13.    (Original) A system as recited in claim 1, wherein the adapter does  
17 not impede the operation of the mobile device.

18  
19           14.    (Original) A system as recited in claim 1, wherein the connector  
20 portion of the host device is standard across a plurality of host devices that are  
21 designed to be used in different environments.

22  
23           15.    (Currently Amended) An apparatus comprising:  
24           a first interface designed to be in communication with an interface of a  
25 mobile device when the apparatus is attached to the mobile device; and

1 a single connector, coupled to the first interface, to allow the apparatus to  
2 be physically attached to and securely held by a plurality of different types  
3 of host devices, wherein the connector includes a second interface to place  
4 the first interface in communication with an interface of one of the plurality  
5 of host devices when the apparatus is physically attached to a host device.

6  
7 **16.** (Original) An apparatus as recited in claim 15, wherein the first  
8 interface and the second interface comprise an electrical interface, wherein the  
9 first interface is designed to be in electrical contact with the interface of the mobile  
10 device, and wherein the second interface is to place the first interface in electrical  
11 contact with the interface of one of the plurality of host devices when the  
12 apparatus is physically attached to the one host device.

13  
14 **17.** (Original) An apparatus as recited in claim 15, wherein the first  
15 interface and the second interface comprise an optical interface.

16  
17 **18.** (Original) An apparatus as recited in claim 15, wherein the  
18 apparatus is designed to securely attach to a mobile device.

19  
20 **19.** (Original) An apparatus as recited in claim 15, wherein the  
21 connector comprises a female jack knife connector.  
22  
23  
24  
25

1           **20.**    (Original) An apparatus as recited in claim 15, wherein the  
2 apparatus is designed to remain continually attached to the mobile device, and  
3 wherein the apparatus does not impede the operation of the mobile device.

4  
5           **21.**    (Original) An apparatus as recited in claim 15, wherein the mobile  
6 device comprises a cellular phone.

7  
8           **22.**    (Original) An apparatus as recited in claim 15, further comprising a  
9 flex circuit that includes both the first interface and the second interface.

10  
11           **23.**    (Original) An apparatus comprising:  
12           a connector to hold an adapter when the adapter is physically attached to  
13 the apparatus, wherein the adapter can be physically attached to a mobile device;  
14 and

15           one or more electrical contacts, situated on the connector and designed to  
16 be electrically coupled to one or more electrical contacts of the adapter when the  
17 adapter is physically attached to the apparatus;

18           wherein the connector is standard across the apparatus and a plurality of  
19 additional apparatus that are designed to be used in different environments.

20  
21           **24.**    (Original) An apparatus as recited in claim 23, wherein the  
22 connector comprises a male jack knife connector.

1           25. (Original) An apparatus as recited in claim 23, wherein the  
2 apparatus comprises a connector assembly including a housing, a connector sub-  
3 assembly that includes the one or more electrical contacts, and a plate holding the  
4 connector sub-assembly in place.

5  
6           26. (Original) An apparatus as recited in claim 23, wherein the mobile  
7 device comprises a cellular phone.

8  
9           27. (Original) An apparatus as recited in claim 23, wherein the  
10 apparatus is designed to be removably coupled to a vehicle.

11  
12           28. (Original) A system comprising:  
13 means for holding a mobile device, the means for holding having means for  
14 electrically interfacing with one or more electrical contacts of the mobile device  
15 when the means for holding is holding the mobile device;

16           means for hosting the means for holding; and

17           means for connecting the means for holding and the means for hosting,  
18 wherein the means for connecting places the means for holding and the means for  
19 hosting in electrical contact with one another, and wherein the means for  
20 connecting further securely attaches the means for holding to the means for  
21 hosting;

22           wherein the means for connecting is standard across a plurality of means  
23 for hosting, and wherein each of the means for hosting is designed to be used in  
24 different environments.  
25

1           29.    (Original) A system as recited in claim 28, wherein the means for  
2 connecting comprises a jack knife connector.

3  
4           30.    (Original) A system as recited in claim 29, wherein the means for  
5 holding further includes a slot of the jack knife connector, and wherein the means  
6 for hosting further includes a blade of the jack knife connector.